Proportional reducing valves

direct, without transducer



RZGE-A



CART RZGE-A

① Valve body
② Poppet
③ Proportional solenoid
④ Screw for air bleeding
⑤ E-MI-AS-IR digital driver (to be ordered separately)

RZGE-A, CART RZGE-A

Poppet type, direct, proportional pressure reducing valves for open loop pressure controls.

They operate in association with off-board driver, which supply the proportional valves with proper current to align the valve regulation to the reference signal supplied to the driver.

They are available in following executions:

RZGE: subplate mounting, ISO size 06
CART RZGE: M20 cartridge execution

The solenoids are certified according to North American standard **cURus**.

Size: **06** - ISO 4401 (RZGE); **M20** (CART RZGE)
Max flow: **12 l/min**
Max pressure: **315 bar**
Max regulated pressure: **210 bar**

For cavity CART RZGE see section 16

1 MODEL CODE

RZGE	-	A	-	010	/	210	-	*	/	*	*	/	*

RZGE
Proportional pressure reducing valve, direct
RZGE = subplate mounting
CART RZGE = cartridge execution

A = for off-board driver, see section 3

Configuration:
010 = reduced pressure on port A

Max regulated pressure:
32 = 32 bar
100 = 100 bar
210 = 210 bar

Coil with special connectors, see section 12 :
- = omit for standard DIN connector
J = AMP Junior Timer connector
K = Deutsch connector
S = Lead Wire connection

Coil voltage, see section 10 :
- = standard coil for 24 VDC Atos drivers
6 = optional coil for 12 VDC Atos drivers
18 = optional coil for low current drivers **(1)**

Series number

Seals material, see section 8 :
- = NBR
PE = FKM
BT = HNBR

(1) Select valve's coil voltage **/18** in case of electronic drivers not supplied by Atos, with power supply 24 VDC and with max current limited to 1,2A

2 HYDRAULIC SYMBOL

RZGE-A
CART RZGE-A



3 OFF-BOARD ELECTRONIC DRIVERS

Drivers model	E-MI-AC-01F **(1)**		E-MI-AS-IR **(1)**		E-BM-AS-PS		E-BM-AES
Type	Analog		Digital				
Voltage supply (VDC)	12	24	12	24	12	24	24
Valve coil option	/6	std	/6	std	/6	std	std
Format	plug-in to solenoid				DIN-rail panel		
Tech table	G010		G020		G030		GS050

(1) For **CART RZGE** the electronic driver may interfere with the manifold surface.
Please check the installation dimensions at section 16

4 GENERAL NOTES

Atos digital proportionals valves are CE marked according to the applicable directives (e.g. Immunity and Emission EMC Directive).
Installation, wirings and start-up procedures must be performed according to the general prescriptions shown in tech table **FS900** and in the installation notes supply with relevant components.

5 GENERAL CHARACTERISTICS

Assembly position	Any position
Subplate surface finishing to ISO 4401	Acceptable roughness index: Ra ≤ 0,8, recommended Ra 0,4 – Flatness ratio 0,01/100
MTTFd valves according to EN ISO 13849	150 years, see technical table P007
Ambient temperature range	**Standard** = -20°C ÷ +70°C **/PE** option = -20°C ÷ +70°C **/BT** option = -40°C ÷ +60°C
Storage temperature range	**Standard** = -20°C ÷ +80°C **/PE** option = -20°C ÷ +80°C **/BT** option = -40°C ÷ +70°C
Surface protection	Zinc coating with black passivation
Corrosion resistance	Salt spray test (EN ISO 9227) > 200 h
Compliance	CE according to EMC directive 2014/30/EU (Immunity: EN 61000-6-2; Emission: EN 61000-6-3) RoHS Directive 2011/65/EU as last update by 2015/863/EU REACH Regulation (EC) n°1907/2006

6 HYDRAULIC CHARACTERISTICS

Valve model	**RZGE-A-010**
Max regulated pressure	32; 100; 210
Min. regulated pressure [bar]	0,8 (or actual value at T port)
Max. pressure at port P [bar]	315
Max. pressure at port T [bar]	210
Max. flow [l/min]	12
Internal leakage [cm³/min]	50 bar = 320; 100 bar =340; 210 bar =550
Response time 0-100% step signal **(1)** (depending on installation) [bar]	≤ 70
Hysteresis [% of the max pressure]	≤ 1,5
Linearity [% of the max pressure]	≤ 5
Repeatability [% of the max pressure]	≤ 2

Note: above performance data refer to valves coupled with Atos electronic drivers, see section 3

(1) Average response time values; the pressure variation in consequence of a modification of the reference input signal to the valve is affected by the stiffness of the hydraulic circuit: greater is the stiffness of the circuit, faster is the dynamic response

7 ELECTRICAL CHARACTERISTICS

Coil voltage code	**Standard** standard coil to be used with Atos drivers with power supply 24VDC	option **/6** optional coil to be used with Atos drivers with power supply 12 VDC	option **/18** optional coil to be used with electronic drivers not supplied by Atos, with power supply 24 VDC and max current limited to 1,2 A
Max. solenoid current	2,5 A	3 A	1,2 A
Coil resistance R at 20°C	3,1 Ω	2,1 Ω	13,1 Ω
Insulation class	H (180°) Due to the occurring surface temperatures of the solenoid coils, the European standards ISO 13732-1 and EN982 must be taken into account		
Protection degree to DIN EN60529	**IP 65** (with connectors 666 correctly assembled)		
Duty factor	Continuous rating (ED=100%)		
Coil certification	**cURus** North American Standards		

8 SEALS AND HYDRAULIC FLUIDS - for other fluids not included in below table, consult our technical office

Seals, recommended fluid temperature		NBR seals (standard) = -20°C ÷ +80°C, with HFC hydraulic fluids = -20°C ÷ +50°C FKM seals (/PE option) = -20°C ÷ +80°C HNBR seals (/BT option) = -40°C ÷ +60°C, with HFC hydraulic fluids = -40°C ÷ +50°C		
Recommended viscosity		20 ÷ 100 mm²/s - max allowed range 15 ÷ 380 mm²/s		
Max fluid contamination level	normal operation	ISO4406 class 18/16/13 NAS1638 class 7		see also filter section at www.atos.com or KTF catalog
	longer life	ISO4406 class 16/14/11 NAS1638 class 5		
Hydraulic fluid		**Suitable seals type**	**Classification**	**Ref. Standard**
Mineral oils		NBR, FKM, HNBR	HL, HLP, HLPD, HVLP, HVLPD	DIN 51524
Flame resistant without water		FKM	HFDU, HFDR	ISO 12922
Flame resistant with water		NBR, HNBR	HFC	

9 DIAGRAMS (based on mineral oil ISO VG 46 at 50 °C)

1 = Regulation diagrams
with flow rate Q = 1 l/min

Note: the presence of counter pressure at port T can affect the effective pressure regulation



2 = Pressure/flow diagrams
with reference signal set at Q = 1 l/min



3-4 = Min. pressure/flow diagrams
with zero reference signal

3 = Pressure drops vs. flow P-A
4 = Pressure drops vs. flow A-T





10 COIL VOLTAGE OPTIONS

6 = Optional coil to be used with Atos drivers with power supply 12 VDC.

18 = Optional coil to be used with electronic drivers not supplied by Atos, with power supply 24 VDC and with max current limited to 1A.

11 AIR BLEEDING

At the first valve commissioning the air eventually trapped inside the solenoid must be bled-off though the screw ① located at the rear side of the solenoid housing.
The presence of air may cause pressure instability and vibrations.



12 COILS WITH SPECIAL CONNECTORS

J option

Coil type COZEJ
AMP Junior Timer connector
Protection degree IP67



K option

Coil type COZEK
Deutsch connector, DT-04-2P male
Protection degree IP67



S option

Coil type COZES
Lead Wire connection
Cable length = 180 mm



13 SOLENOID CONNECTION

PIN	SIGNAL	TECHNICAL SPECIFICATION	Connector code 666
1	**COIL**	Power supply	
2	**COIL**	Power supply	
3	**GND**	Ground	

14 FASTENING BOLTS AND SEALS FOR RZGE



Fastening bolts:
4 socket head screws M5x50 class 12.9
Tightening torque = 8 Nm

Seals:
3 OR 108
Diameter of ports P, T, A: Ø 5 mm
Port B not used

15 INSTALLATION DIMENSIONS FOR RZGE [mm]

ISO 4401: 2005
Mounting surface: 4401-03-02-0-05 (see table P005)
(without port B)

Mass [kg]	
RZGE	1,5
RZGE with E-MI-AS-IR	2,0



Valve's bottom view

RZGE-A





RZGE-A
(with E-MI-AS-IR digital driver)





(1) = Air bleeding, see section 11

16 INSTALLATION DIMENSIONS FOR CART RZGE [mm]

Cavity dimensions for **CART RZGE-A**



CART RZGE-A



CART RZGE-A
(with E-MI-AS-IR digital driver)



To be checked
for eventual interference
with the manifold surface





Mass [kg]	
CART RZGE	0,6
CART RZGE with E-MI-AS-IR	1,1